LD PUMPED ALL-SOLID-STATE GREEN LASER

RN-W-532/5~20W



YANBAN LASER

All solid state 532nm green laser is made features of ultra compact, long lifetime,

and easy operating, which is widely used in collimation, laser medical treatment,

scientific experiment, optical instrument, laser display, laser lighting show, etc



RN-W-532	2/5~20W	
Wavelength (nm)	532±1	
Operating mode	CW	
Output power (W)	>5, 5.5, 6,, 20	
Power stability (rms, over 4 hours)	<1%, <2%, <3%,<5%	
Transverse mode	TEM ₀₀	
M ² factor	3~6 (5W~13W)	F
Beam divergence, full angle (mrad)	<1.5	№
Beam diameter at the aperture (1/e ² ,mm)	~4.0	Ł
Warm-up time (minutes)	<10	•
Beam height from base plate (mm)	93.5	
Polarization ratio	>50:1(<100:1 optional)	
Operating temperature ($^{\circ\!$	10~35	
Power supply (90-264VAC)	PSU-W-LED/PSU-W-FDA	
TTL / Analog modulation	TTL on/off, 1Hz-1KHz, 1KHz-10KHz, 10KHz-30KHz; and Analog modulation option	
Expected lifetime (hours)	10000	
Warranty	1 year	

北京市昌平区 国家信息产业基地立业路13号2011 ≤ sales@ranbond.com

