

DIODE XS SERIES LASER AT 505nm

RN-III-505L/1~80mW

产品描述

It features ultra compact design, long lifetime, cost-effectiveness and easy operation. They are widely used in biological, medical, laser pumping, scientific research, etc.

产品参数

RN -III-505L/1~80mW		
Central wavelength (nm)	505±5	
Operating mode	CW	
Output power (mW)	>1,2, ..., 20	>20, 30, ..., 80
Power stability (rms, over 4 hours)	<1%, <2%, <3% (<0.5%, optional)	
Transverse mode	Near TEM ₀₀	
M ² factor	<1.5 (<1.2, optional)	
Beam divergence, full angle (mrad)	~2.5 (~1.2, optional)	
Beam diameter at the aperture (1/e ² ,mm)	0.5	
Polarization ratio	>50:1 (>100:1, optional) Horizontal±5 degree (Vertical Optional)	
Beam height from base plate (mm)	24.8	
Warm-up time (minutes)	<5	
Operating temperature (°C)	10~35	
Power supply	85-264VAC	PSU-III-LED/ PSU-III-FDA (Frequency for 1Hz-30kHz)
	100-240VAC	PSU-A-D (Frequency for 30kHz -100kHz)
TTL / Analog modulation	TTL or Analog with 1Hz-1kHz 1kHz-10kHz, 10kHz-30kHz, 30kHz-100kHz optional	
Expected lifetime (hours)	10000	
Warranty period	1 year	

