

LD PUMPED ALL-SOLID-STATE GREEN LASER AT 523.5nm

RN-FN-523.5/1~800mW

产品描述

All solid state 523.5nm green laser is made features of high output power stability, good beam profile, ultra compact, long lifetime, cost-effectiveness and easy operating, which is widely used in collimation, laser medical treatment, scientific experiment, optical instrument, etc.

产品参数

RN-FN-523.5/1~800mW		
Central wavelength (nm)	523.5±1	
Operating mode	CW	
Output power (mW)	>1, 10, 50, ... , 400	>400, ..., 800
Power stability (rms, over 4 hours)	<2%, <3%, <5%	<3%, <5%, <10%
Transverse mode	Near TEM ₀₀	
M ² factor	<1.5	
Beam diameter at the aperture 1/e ² (mm)	~2.0	
Beam divergence, full angle (mrad)	<1.5	
Polarization ratio	>100:1 Horizontal±5 degree (Vertical Optional)	
Warm-up time (minutes)	<10	
Pointing stability after warm-up (mrad)	<0.05	
Beam height from base plate (mm)	27.4	
Operating temperature (°C)	10~35	
Power supply (90-264VAC)	PSU-H-LED/PSU-H-FDA/PSU-SR	
Modulation option	TTL on/off, 1Hz-1KHz, 1KHz-10KHz, 10KHz-30KHz; and Analog modulation option	
Expected lifetime (hours)	10000	
Warranty	1 year	

