

## BLUE DIODE LASER AT 442nm

RN-III-442/80~1000mW

### 产品描述

It features ultra compact design, long lifetime, cost-effectiveness and easy operation.

They are widely used in scientific research, laser pointing, measurement, communication, spectrum analysis, etc.

### 产品参数

RN-III-442/80~1000mW		
Central wavelength (nm)	442±5	
Operating mode	CW	
Output power (mW)	>80,90,....,500	>500,600,....,1000
Power stability (rms, over 4 hours)	<1%, <2%, <3% (<0.5%, optional)	
Transverse mode	Multimode	
Beam divergence, full angle (mrad)	<2.5×5.2	<2×5
Beam diameter at the aperture (1/e <sup>2</sup> ,mm)	<2.1×1.6	<2.5×0.2
Warm-up time (minutes)	<5	
Beam height from baseplate (mm)	24.8	
Operating temperature (°C)	10~35	
Power supply	85-264VAC	PSU-III-LED/ PSU-III-FDA (Frequency for 1Hz-30kHz)
	100-240VAC	PSU-A-D (Frequency for 30kHz -100kHz)
TTL / Analog modulation	TTL or Analog with 1Hz-1kHz 1kHz-10kHz, 10kHz-30kHz, 30kHz-100kHz optional	
Expected lifetime (hours)	10000	
Warranty	1 year	