

## LD PUMPED ALL-SOLID-STATE RED LASER

RN-S-671 /1~200mW

### 产品描述

All solid state laser at 671nm is made features of ultra compact, small size, wide operating temperature, good sealing, long lifetime, cost-effectiveness and easy operating, working under the pressure of 0.02kPa, which is widely used in measurement, spectrum analysis, and laser lighting show, etc.

### 产品参数

RN-S-671 /1~200mW				
Model	MRL-S-671-A(Harsh condition)		MRL-S-671-B (Normal condition)	
Central wavelength (nm)	671±1			
Operating mode	CW			
Output power (mW)	>1, 5, 10, 20, ... , 100	100, ... ,200	>1, 5, 10, 20, ... , 100	100, ... ,200
Power stability (rms, over 4 hours)	<1%, <2%, <3%	<2%, <3%	<1%, <2%, <3%	<2%, <3%
Transverse mode	TEM00			
M2 factor	<1.2(<1.1 optional)		<1.2	
Beam diameter at the aperture (1/e <sup>2</sup> ,mm)	0.7±0.05			
Beam divergence, full angle (mrad)	<1.5			
Polarization ratio	>100:1 Horizontal±5 degree (Vertical Optional)			
Pointing stability after warm-up (mrad)	<0.05			
Pointing stability Over Temp. (μrad/°C)	<8			
Warm-up time (minutes)	<5			
Beam height from base plate (mm)	19			
Power Consumption(W)	<30			
Shock Tolerance(6ms)	7g laterally,15g vertically			
IP Rating	IP67		IP65	
Power supply(90-264VAC)	PSU-H-FDA		PSU-A-DP	PSU-A-FP PSU-III-OEM-97 (5VDC)
Operating temperature (°C)	0-60		10-35	
Max. Heat Dissipation of Head(W)	10W@50°C		4W@25°C	
Modulation	TTL on/off, 1Hz-1KHz, 1KHz-10KHz, 10KHz-30KHz; and Analog modulation option			
Expected lifetime (hours)	10000			
Warranty	1 year			